

FireWire IEEE 1394 Cable (6pin/6pin M/M) 15 ft. (4.57 m)

MODEL NUMBER: F005-015



Features

- All Tripp Lite Firewire (IEEE 1394) cabling includes superior foil shielding for reliable error-free data
- Firewire cable meets IEEE 1394 standards as set by the institute of electrical and electronic engineers.
- Premium quadruple-shielded cables with tinned copper braid and aluminum
- Mylar foil on each twisted pair as well as on the cable as a whole.
- Gold plated connectors provide superior conductivity.
- Supports data transmission of 100~400Mbps

Specifications

OVERVIEW		
UPC Code	037332011985	
Technology	FireWire	
PHYSICAL		
Color	Black	
Cable Length (ft.)	15	
Cable Length (m)	4.6	
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	

Highlights

- Premium quadruple-shielded cables with tinned copper braid and aluminum mylar foil on each twisted pair as well as on the cable as a whole
- Gold plated connectors provide superior conductivity

System Requirements

 Two Firewire IEEE 1394 devices each with 6 Pin Female connectors.

Package Includes

15-ft. Firewire IEEE 1394
 6Pin/6Pin with Gold Connectors



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Shipping Weight (kg)	0.23	
Shipping Weight (lbs.)	0.51	
CONNECTIONS		
Side A - Connector 1	6 PIN (MALE)	
Side B - Connector 1	6 PIN (MALE)	
STANDARDS & COMPLIANCE		
Certifications	RoHS-Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies