

4 Port Rack Mountable USB KVM Switch with Audio & USB 2.0 Hub

Product ID: SV431USBAE



This Rack Mountable USB KVM Switch supports high resolution video applications (up to 1920x1440 pixels supported) and audio switching between connected computers, and provides an integrated USB 2.0 hub that lets the selected computer have access shared high speed USB peripherals.

Providing control of up to four computers from a single USB keyboard and mouse peripheral set, the switch features a sturdy all metal chassis and can be rackmounted in a server rack/cabinet using an optional Rackmount Bracket kit (SV431RACK) - minimizing clutter and saving space.

This product is TAA compliant and is backed by a StarTech.com 3 year warranty with lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Control up to four computers, sharing a single keyboard, mouse, monitor and speakers.
- Integrated USB 2.0 hub allows you to share up to three USB peripherals between the four computers.

Features

- Designed for high-resolution applications: up to 1920x1440 pixels supported
- All metal chassis for long-term durability
- Integrated USB 2.0 hub allows you to share up to three high-speed USB devices between computers
- · Audio switching with microphone and speaker connectivity



- Auto-scan function automatically selects computer sequentially
- Compatible with all USB supported Operating Systems
- Front panel push button computer selection

| Hardware | | |
|-------------|---------------------------------|--------------|
| | Warranty | 3 Years |
| | U Height | 1U |
| | Audio | Yes |
| | KVM Ports | 4 |
| | PC Interface | USB |
| | PC Video Type | VGA |
| | Number of Monitors Supported | 1 |
| | Rack-Mountable | Optional |
| | Cables Included | No |
| | Daisy-Chain | No |
| Performance | | |
| | On-Screen Display | No |
| | DVI Support | No |
| | IP Control | No |
| | Hot-Key Selection | No |
| | Maximum Analog Resolutions | 1920x1440 |
| | Maximum Number of Users | 1 |
| | Port Selection Support | Push Button |
| | MTBF | 136000 hours |

Connector(s)



Console Interface(s) VGA (15 pin, High Density D-Sub)

USB Type-A (4 pin) USB 2.0

3.5 mm Mini-Jack (3 Position)

Host Connectors VGA (15 pin, High Density D-Sub)

USB B (4 pin)

3.5 mm Mini-Jack (3 Position)

Other Interface(s) USB Type-A (4 pin) USB 2.0

Software

OS Compatibility OS independent; No software or drivers required

Power

Power Source AC Adapter Included

10

Input Voltage 100 - 240 AC

Input Current 0.4A

Output Voltage 5 DC

Output Current 2A

Center Tip Polarity Positive

Plug Type N

Power Consumption (In

Watts)

Physical Characteristics

Color Black

Material Steel

Product Length 8.7 in [22 cm]

Product Width 5.1 in [13 cm]

Product Height 1.8 in [44.5 mm]

Weight of Product 2.2 lb [1.0 kg]



Packaging Information

Package Length 9.6 in [24.5 cm]

Package Width 16.3 in [41.3 cm]

Package Height 3.5 in [90 mm]

Shipping (Package)

Weight

3.3 lb [1.5 kg]

What's in the

Box

Included in Package 4 Port USB KVM Switch With Audio

Pack Rubber Feet

Power Adapter

Manual

^{*}Product appearance and specifications are subject to change without notice.