HSM[®] SECURIO

B34 Office shredder Large Volume, High Performance



- Energy Management Control System Eco Smart: particularly low power consumption of 0.1 watt in standby mode
- Automatically switches to energy-saving mode in 2 minutes after last use; switches off entirely if not used for 1 hour; temporary mode for small shredding jobs; and permanent mode for large shredding jobs
- Multifunctional control key with reversing function
- Shred bin level indicator
- Removable CD waste container on Level 2 and 3 models
- Folding safety element
- Cutting rollers are V-TEK by HSM with specially hardened steel rollers. This optimum design of all cutting unit components saves valuable energy.
- Continuous motor operation
- Quiet Operation feature shreds documents with a pleasantly quiet operating sound
- Equipped with Anti-Jam technology to easily and quickly reverse out paper in the event the machine is overloaded
- Optional: Automatic oiler for cross-cut and micro-cut ensures long time cutting performance and quality

• 34 gallon waste bag capacity; Part #HSM1815

		CERMANT STEEL CUTTING AS	R CUTTING PARTIES PARTIES	AND PLATOPERATOR PRETY SYSTEM
HSM part#	HSM1840	HSM1841	HSM1843	HSM1842
Cutting type	Strip cut	Strip cut	Cross cut	Micro cut
Cutting size	1/8″	1/4″	3/16" x 1 1/8"	1/16″ x 9/16″
Security level DIN 32757-1	2	2	3	4
Security level DIN 66399	P-2 / O-2 / T-2 / E-2	P-2 / O-2 / T-2 / E-2	P-4 / O-3 / T-4 / E-3 / F-1	P-5 / T-5 / E-4 / F-2
Cutting capacity per run in sheets	28 - 30	35 - 37	22 - 24	13 - 15
Cutting speed	17 ft / min	17 ft / min	17 ft / min	17 ft / min
Throat opening	12.2″	12.2″	12.2″	12.2″
Motor at max. no. of sheets	650W	650W	650W	650W
Motor power (horsepower)	0.87	0.87	0.87	0.87
Voltage	115 V / 60 Hz	115 V / 60 Hz	115 V / 60 Hz	115 V / 60 Hz
Dimensions (H x W x D)	33.3″ x 21.3″ x 17.3″	33.3" x 21.3" x 17.3"	33.3" x 21.3" x 17.3"	33.3″ x 21.3″ x 17.3″
Weight	72 lbs	72 lbs	77 lbs	77 lbs
Shred-bin volume	26.4 gallons	26.4 gallons	26.4 gallons	26.4 gallons
Cutting capabilites	Ď Ø Ħ • I Į	<u>т</u> е с	Ď Ø Ħ • I Į	

All technical specifications are approximate values. Technical and design modifications reserved.

HSM of America, LLC 419 Boot Road Downingtown, PA 19335 www.hsmofamerica.com Customer Service: 800.613.2110



