

4 Port 1U Rackmount USB KVM Switch with OSD

Product ID: SV431DUSBU



The SV431DUSBU 4 Port 1U Rack Mountable USB KVM Switch with OSD lets you control multiple USB based computers from a single console (USB keyboard, USB mouse, monitor).

Convenient push-button and hot-key controls provide quick, reliable switching between connected computers while manual and auto-scan switching modes and an On Screen Display (OSD) offer additional control options.

Designed to ensure maximum space efficiency, the USB KVM switch features a slim 1U design that fits neatly into a server equipment rack/cabinet (with optional mounting bracket SV431RACK) and offers rear cable connections to eliminate cable tangles and minimize workspace disruption.

This product is TAA compliant and backed by a Startech.com 3-year warranty with free lifetime technical support.

If you'd like to mount this KVM switch to your server rack, StarTech.com offers a 1U Rackmount Bracket (sold separately) that turns this KVM into a rackmountable KVM.

The SV431DUSBU only works with specific 2-in-1 VGA and USB cables (sold separately), a list of StarTech.com approved cables are below:

6 ft Ultra Thin USB VGA 2-in-1 KVM Cable

6 ft Ultra Thin USB VGA 2-in-1 KVM Cable

10 ft Ultra Thin USB VGA 2-in-1 KVM Cable

15 ft Ultra Thin USB VGA 2-in-1 KVM Cable

Certifications, Reports and Compatibility



Applications

- Add single console administration to your Co-location/ISP facility saving you time and money
- Create a scalable, streamlined access solution in your Datacenter or Server Farm
- Perfect for manufacturing line computer control, simplifying access to multiple systems
- Great for PC test/burn-in computer control saving the desk space required for multiple monitors, keyboards and mice
- Ideal for control of multiple PCs in a QA testing environment

Features

- OS Independent No drivers or software required
- Auto-scan function automatically selects computer sequentially
- Front panel push-button and Hotkey switching allow easy computer access
- Identifies and selects computers by the names assigned using the OSD
- USB console connections
- Rename connected computers for easy identification
- OSD security allows each PC to be password protected
- Plug-and-play system configuration
- Supported Wide Screen Resolutions: 1920x1200, 1920x1080, 1680x1050, 1400x1050, 1440x900, 1360x768
- Supported 4 : 3 Resolutions: 1920x1440, 1600x1200, 1280x1024, 1024x768

Hardware		
	Warranty	3 Years
	Audio	No
	KVM Ports	4
	PC Interface	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	Optional



	Cables Included	No
	Daisy-Chain	Yes
Performance		
	On-Screen Display	Yes
	DVI Support	No
	IP Control	No
	Hot-Key Selection	Yes
	Maximum Analog Resolutions	1920 x 1440@60Hz (1920 x 1200@60Hz - Wide Screen)
	Wide Screen Supported	Yes
	Maximum Number of Users	1
	Port Selection Support	Push Button, Hotkeys, and OSD (On Screen Display)
	MTBF	143000 hours
Connector(s)		
	Console Interface(s)	VGA (15 pin, High Density D-Sub)
		USB Type-A (4 pin) USB 2.0
	Host Connectors	VGA (15 pin, High Density D-Sub)
Software		
	OS Compatibility	OS independent; No software or drivers required
Indicators		
	LED Indicators	Green - Power
		Green - Online PC
		Red - Selected PC
Power		
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC



Input Current 0.2A

Output Voltage 9V DC

Output Current 0.6A

Center Tip Polarity Positive

Plug Type M

Power Consumption (In 5

Watts)

Environmental

Operating Temperature 5C to 40C (41F to 104F)

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 80% RH

Physical Characteristics

Color Black

Material Steel

Product Width 8.7 in [22 cm]

Product Height 1.7 in [43 mm]

Product Depth 5.1 in [13 cm]

Weight of Product 33.8 oz [957 g]

Packaging Information

Package Length 8.5 in [21.5 cm]

Package Width 16.2 in [41.1 cm]

Package Height 3.5 in [89 mm]

Shipping (Package)

Weight

3.5 lb [1.6 kg]

What's in the Box

Included in Package 4-port KVM switch



foot pads

universal power adapter (NA/EU/UK/AU)

instruction manual

^{*}Product appearance and specifications are subject to change without notice.