



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Isobar 12-Outlet Network Server Surge Protector, 15 ft. (4.57 m) Cord with 5-20P Plug, 3840 Joules, Diagnostic LEDs, 1U Rack-Mount

MODEL NUMBER: IBAR12-20ULTRA



Rack-mount protection for A/V components, network hardware, retail displays, appliances, power tools and other expensive electronics against dangerous surges, spikes and line noise in IT and industrial environments.

Features

Network-Grade 3840-Joule Surge Protection for IT or Industrial Electronics Protects rack-mounted network hardware, retail displays, appliances, power tools and other expensive electronics against even the strongest surges and spikes Recommended for network workstations, telecom systems, point-of-sale equipment and audio/video systems requiring AC line protection Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss Exceeds IEEE 587 Category A and B surge suppression specifications

12 Outlets Accept Wide Range of Electronic Devices 2 NEMA 5-15R in front, 10 NEMA 5-20R in rear AC outlets accept most computer, networking and telecom equipment

Isolated Filter Banks Provide Extra Protection Outlets arranged in 2 exclusive isolated filter banks to limit noise interaction among connected equipment Block disruptive EMI/RFI line noise that can cause equipment damage or data loss

Premium Safety Features Lighted on/off switch with locking cover provides one-touch control over connected equipment Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required Diagnostic LEDs confirm power, protection and line fault status at a glance Conforms to current UL 1449 3rd Edition safety standards

Flexible Mounting Options Mounts into 1U of space in EIA-standard 19 in. racks Included mounting hardware also allows installation on wall or under counter Long 15-ft. (4.57 m) AC power cord with NEMA 5-20P plug reaches distant outlets All-metal housing designed for long life

Backed by Tripp Lite's Ultimate Lifetime Insurance \$25,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Highlights

- 2 NEMA 5-15R & 10 NEMA 5-20R outlets in isolated filter banks
- Network-grade 3840-joule surge protection rating
- Mounts into 1U of space in EIA-standard 19 in. racks
- 20A resettable circuit breaker prevents dangerous overloads
- 15-ft. (4.57 m) AC power cord with NEMA 5-20P plug

Package Includes

- IBAR12-20ULTRA Isobar 12-Outlet Surge Protector, 1U Rack-Mount
- Rack-mounting brackets
- Owner's manual

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332099235 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| INPUT | |
|-------------------------------------|--|
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 150000 |
| Input Plug Type | NEMA 5-20P |
| Input Cord Length (ft.) | 15 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 4.57 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 2400 |
| Output Receptacles | (12) 5-15R |
| Circuit Breaker (amps) | 20 |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Switches | Red illuminated power switch controls power to all outlets |
| Diagnostic LED Details | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green) |
| Locking Switch Cover | Transparent locking switch cover prevents accidental shutoff |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 3840 |
| AC Suppression Response Time | NM = 0 ns. CM = <1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping Voltage (RMS) | 140 |
| AC Suppression Surge Current Rating | 96,000 amps |
| AC Suppression Components Used | Metal oxide varistors, toroidal balanced chokes and VHF capacitors |
| Safe Thermal Fusing | Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurrences |
| UL1449 Let Through Rating | 330V |
| EMI / RFI Filtering | 40-80 dB |
| Isolated Filter Banks | 2 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|---|
| Immunity | Conforms to IEE 587 / ANSI C62.41 |
| Automatic Shut-Off | No |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Color | Black |
| Antimicrobial Coating | No |
| Color (AC Line Cord) | Black |
| Form Factors Supported | 1U rackmount, 0U vertical rackmount, wallmount and under-counter mounting supported - detachable flanges can be re-configured to support a variety of additional mounting options |
| Housing Color | Black |
| Included Mounting Accessories | Included mounting flanges are pre-installed for 1U rackmount installation and can be re-configured to support a variety of mounting options |
| Integrated Keyhole Mounting Slots | Yes (Includes flanges) |
| Material of Construction | Metal |
| Outlets Measurement (Center to Center) | Distance between front outlets = 38.9mm; Distance between rear outlets = 40.65mm |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / cm) | 23.37 x 6.60 x 51.56 |
| Shipping Dimensions (hwd / in.) | 9.20 x 2.60 x 20.30 |
| Shipping Weight (kg) | 2.99 |
| Shipping Weight (lbs.) | 6.60 |
| Unit Dimensions (hwd / cm) | 4.45 x 44.45 x 10.16 |
| Unit Dimensions (hwd / in.) | 1.75 x 17.5 x 4 |
| Unit Weight (kg) | 2.86 |
| Unit Weight (lbs.) | 6.3 |
| SPECIAL FEATURES | |
| Rotatable Outlets | No |
| STANDARDS & COMPLIANCE | |
| Canada | Approved for Canada by ETL |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| UL1449 3rd Edition (AC Suppression) | Tested to UL1449 3rd Edition by ETL |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| WARRANTY | |
|--|---|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 Ultimate Lifetime Insurance |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>