

# Product data sheet

Specifications



## APC SERVICE BYPASS PDU, 120V 20AMP W/ (6) NEMA 5-15R AND (2) 5-20R

SBP2200RM

Product availability: Stock - Normally stocked in distribution facility

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Product or Component Type	Bypass kit
Main Output Voltage	120 V
Input Connection Type	NEMA 5-20P
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	1
Provided Equipment	User Manual Rack Mounting brackets

### Physical

Color	Black
Height	3.5 in (8.9 cm)
Width	17.008 in (43.2 cm)
Depth	3.0 in (7.6 cm)
Net Weight	6.50 lb(US) (2.95 kg)
mounting location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted

### Input

Input Frequency	50/60 Hz
Acceptable Input Voltage	100...125 V
Max line current	20 A
Input current limits	20 A
Load Capacity	2200 VA
Load Power Factor Range	0...1

### Output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum Total Current Draw per Phase	20 A
Number of power socket outlets	6 NEMA 5-15R 2 NEMA 5-20R
Number of power socket outlets	10
Protection Type	Circuit breaker
Cord Length	4 ft (1.2 m)
Efficiency	99 %

## Conformance

Product Certifications	TÜV
------------------------	-----

## Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304266754
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.9 in (15.1 cm)
Package 1 Width	11.6 in (29.5 cm)
Package 1 Length	18.2 in (46.3 cm)
Package 1 Weight	8.4 lb(US) (3.8 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Reach Regulation		<a href="#">REACH Declaration</a>
Eu Rohs Directive		Compliant <a href="#">EU RoHS Declaration</a>
China Rohs Regulation		<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)