

HSM® Classic

125.2 document shredder

Ideal in central location for a mid-size, busy office



- Automatic start/stop control via electronic eye
- Reverse button to release overfed paper
- Auto stop and container full indicators
- Ideal for 6-11 person office in need of a centralized shredder
- Hardened 100% solid steel cutters can handle occasional standard paper clips or staples
- Motor with thermal protection
- Powerful, specially adjusted drive for high performance and longer periods of use
- Cutting rollers with patented V-groove technology; complete with a lifetime warranty
- Tried and tested closed-tooth wheel drive prevents penetration of dirt and slows wear, increasing service life
- Enclosed housing protects against the spread of paper dust
- Cross cut and micro cut shredders should be oiled regularly to maintain top working condition
- Optional auto oiler available for cross cut and micro cut models
- Uses a 34 gallon capacity shred bag; Part #HSM1815



| HSM part# | HSM1272 | HSM1274 | HSM1275 |
|------------------------------------|-----------------------------|-----------------------------|-----------------------------|
| Cutting type | Strip cut | Cross cut | Micro cut |
| Cutting size | 1/4" | 1/8" x 1 1/8" | 1/32" x 7/16" |
| Security level DIN 32757-1 | 2 | 3 | 5 |
| Security level DIN 66399 | P-2 / O-2 / T-2 / E-2 | P-4 / T-4 / E-3 / F-1 | P-6 / F-3 |
| Cutting capacity per run in sheets | 28 - 30 | 16 - 18 | 6 - 7 |
| Cutting Speed | 24 ft / min | 28 ft / min | 26 ft / min |
| Throat opening | 10" | 10" | 10" |
| Motor at max. no. of sheets | 670W | 670W | 670W |
| Motor power (horsepower) | 0.90 | 0.90 | 0.90 |
| Voltage | 115 V / 60Hz | 115 V / 60Hz | 115 V / 60Hz |
| Dimensions (H x W x D) | 32 3/5" x 17 3/5" x 13 3/5" | 32 3/5" x 17 3/5" x 13 3/5" | 32 3/5" x 17 3/5" x 13 3/5" |
| Weight | 57 lbs | 66 lbs | 66 lbs |
| Shred-bin volume | 20 gal | 20 gal | 20 gal |
| Cutting capabilities | | | |

All technical specifications are approximate values. Technical and design modifications reserved.
 *Anti-Jam Auto Reverse function available on the cross and micro-cut versions only.

HSM of America, LLC
 419 Boot Road
 Downingtown, PA 19335
www.hsmofamerica.com
 Customer Service: 800.613.2110

Great Products, Great People.

HSM®