

ZUM DECT 6.0 Headset™

DIGITAL ENHANCED CORDLESS TELECOMMUNICATIONS



ZuM DECT 6.0 Headset™ with Over the Head headband



ZuM DECT 6.0 Headset™ with Over the Head headband

ZuM DECT 6.0 Headset™ with Ear Hanger

Designed for multiple user environments, the ZUM DECT 6.0 Headset™ allows wireless telephone conversations without the limitations of Bluetooth®. Unlike Bluetooth®, the ZUM DECT 6.0 Headset™ operates on the secure DECT 6.0 Protocol. The range is up to 500 feet, as opposed to Bluetooth®'s 30 feet. The number of users is practically unlimited, compared with the 55 user maximum limit of Bluetooth®. But anyone can benefit from the comfortable headset with noise cancellation and the ability to be able to walk away from the phone while continuing the conversation. The Base Unit recharges the headset and will work up to 7 hours on one charge. There is a Remote Handset Lifter RHL-2010 (sold separately) available which allows you answer and hang up even if you're not near the phone.

If you spend a lot of time on the phone, this product will give you flexibility and freedom you never had before.

Features Include:

- Compatibility: DECT GAP VoIP
- US, Canada, Europe, Latin America Compatible Frequencies and certifications
- Secure DECT 6.0 Protocol
- Use over the head headset or ear hanger
- Active DSP noise cancellation microphone
- Full Duplex for simultaneous conversations
- Low Emissions - Dynamic signal power adjustment. Adjusts for lowest emissions based on proximity to base station
- Rechargeable Li Ion battery; up to 7 hours talk time
- DECT 6.0 headset with built in recharger station



ZuM DECT 6.0 Headset™ shown with Remote Handset Lifter (sold separately) and desktop phone

ZuM DECT 6.0 Headset™

DIGITAL ENHANCED CORDLESS TELECOMMUNICATIONS

2672 Bayshore Parkway :: Bldg 900 | Mountain View, CA 94043 USA | p.: 650.215.7500 | f.: 650.318.8060 | www.spracht.com



PRODUCT SPECIFICATIONS		HS-2012	
Features		Controls and Interfaces	
Compatibility: DECT	GAP VoIP	Base Unit	Headset
Secure DECT 6.0 protocol		Listening Volume Up/Down	In Use
DSP (Digital Signal Processing) based noise cancellation		Microphone Volume Up/Down	Standby
Noise Cancelling Microphone		Configuration Dial Settings A to G	Register
Supports three way and conference calling		Mute In Use	Mute On
High Performance mini speaker		Register	Register
Over the Head Headband or Ear Hanger		Battery Level Indicator	Out of Range
Package includes		In Use LED	Low Battery
P/N: HS-2012		Electrical, Audio Specifications	
ZuM DECT 6.0 Headset™		Operating frequency: 1920-1930 MHz USA Standard, 1910-1930 MHz Latin America, 1880-1900 MHz Europe	
ZuM DECT 6.0 Headset™ Base with Built In Recharger		Dynamic Power Adjustment: Strength of the DECT signal is adjusted by the Base Unit depending on the proximity of the Headset to the Base Unit	
Over the Head Headband		Rechargeable Li Ion Battery: up to 7 hours Talk, 120 hours Standby, 3.7VDC/320mAh	
Ear Hanger		Charge Time: 3 hours	
Cushion Ear Covers		Certifications: FCC, CE	
RJ-11 Phone Cord			
AC Power Adapter			
Users Guide / Registration Card			
Mechanical Specifications			
Dimensions Base	2.71" (69 mm) L x 2.56" (65 mm) D x 4.76" (121 mm) H	Package is approximately 8.86" (225mm) L x 3.15" (80mm) D x 5.63" (143mm) H	
Dimensions Headset	5.7" (145 mm) L x .79" (20 mm) D x 1.1" (28 mm) W	1 year limited warranty	
Weight Headset w/batt.	.98 oz. (28 gm)	Boxed Weight 24oz (680gm)	
Weight Headband	.63 oz. (18 gm)	UPC 800807320086	
Operating Temperature	32° - 104° F (0° C to 40° C)		



ZuM DECT 6.0 Headset™ Packaging Sleeve
Front and Side View

ZuM DECT Headset HS-2012 ver USA



8 00807 32008 6