



Microsemi® Adaptec® Trusted Storage Solutions

A complete portfolio of 12 Gbps Host Bus Adapters, RAID Adapters,
SAS Expander and Cables

Microsemi Adaptec HBA 1000 Series PCIe Gen 3 12 Gbps Host Bus Adapter

The new Microsemi Adaptec HBA 1000 Series of Host Bus Adapters delivers the smart connectivity that businesses are looking for with an optimal mix of resiliency, efficiency, and ease of use. It's an ideal solution for server-based storage systems that require maximum bandwidth and I/O connectivity, low power, and high reliability.

Available in five different 12 Gbps configurations with up to 16 internal or 16 external SAS/SATA ports, it offers the highest port count at the lowest power in a low-profile, MD2 form factor.

- **New unified Smart Storage Stack** that delivers resiliency by combining the best of the eighth-generation Adaptec ARC software and drivers with the acquired Smart IP of the most broadly deployed server storage stack. The result is a robust and stable stack with common easy-to-use management tools, drivers, and interface
- **Microsemi SmartIO SAS/SATA protocol controller** that drives efficiency of higher performance, maximum port count and 60% less power consumption, on average, than competing HBAs
- **Performance** of up to 1.3M IOPS, low latency, and bandwidth that fully saturates the PCIe Gen3 bus
- **Scalability** with up to 16 native internal or 16 native external SATA/SAS ports
- **Broad ecosystem compatibility**, including 6 Gbps systems

The HBA 1000 Series is the first of the Microsemi Adaptec Smart Storage Solutions family and the newest addition to the 12 Gbps storage product portfolio, which includes the award-winning Adaptec Series 8 RAID adapters, Adaptec SAS expander, and mini-SAS HD cables. Microsemi has the Smart Storage Solution for the data center and enterprise of today – and tomorrow.



12 Gbps

Smart Storage Solutions for Your Server-Based Storage Needs

Today's data centers and enterprises continue to search for resilient, efficient, and easy-to-use storage solutions capable of keeping pace with their accelerating data expansion. Advances in SSD performance and HDD capacities require smart storage solutions. Solutions that can manage data effectively, integrate seamlessly, and offer proven compatibility with multiple operating systems versions, as well as numerous current and future server and enclosure brands and models.

Created through the convergence of Microsemi's silicon expertise, 30+ years of innovative Adaptec board designs, and a robust, enterprise-ready Smart Storage Stack, these Microsemi® Adaptec® Smart Storage Solutions are a new generation of products that deliver the highest I/O performance, highest density, lowest power consumption per port and the lowest total cost of ownership.

Microsemi Adaptec Smart Storage Solutions are the next step in Microsemi's history of developing leading storage innovations. Delivering resiliency, efficiency, and ease of use across the entire new solution family, Microsemi Adaptec Smart Storage Solutions will provide the most compelling customer value. Starting with the HBA 1000, available today, these future products will be fully compatible with the current portfolio of Microsemi Adaptec HBA, RAID, and expander solutions.



Smart
Storage Solutions





Microsemi Adaptec Host Bus Adapters:

	Adaptec HBA 1000-16i	Adaptec HBA 1000-16e	Adaptec HBA 1000-8i8e	Adaptec HBA 1000-8i	Adaptec HBA 1000-8e
Ordering Part Number	Single: 2288400-R	Single: 228200-R	Single: 2288500-R	Single: 2288300-R	Single: 2288100-R



	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3
Bus Interface	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3	8-lane PCIe Gen3
Processor	Microsemi SmartIOC	Microsemi SmartIOC	Microsemi SmartIOC	Microsemi SmartIOC	Microsemi SmartIOC
Form Factor	MD2 - Low Profile	MD2 - Low Profile	MD2 - Low Profile	MD2 - Low Profile	MD2 - Low Profile
Dimensions	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)
Ports	16 Internal	16 External	8 Internal/8 External	8 Internal	8 External
Maximum Scalability	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*
Connector	4 Internal SFF-8643	4 External SFF-8644	2 Internal SFF-8643 2 External SFF-8644	2 Internal SFF-8643	2 External SFF-8644
Power Consumption (typ)	11.8 W	11.1 W	12.3 W	9.4 W	8.7 W

HBA

Microsemi Adaptec 12 Gbps and 6 Gbps RAID Adapters:

	Adaptec RAID 81605ZQ	Adaptec RAID 8885Q	Adaptec RAID 81605Z	Adaptec RAID 8885	Adaptec RAID 8805	Adaptec RAID 8405	Adaptec RAID 71605Q	Adaptec RAID 7805Q
Ordering Part Number	Single: 2281600-R	Single: 2277100-R	Single: 2287101-R	Single: 2277000-R	Single: 2277500-R	Single: 2277600-R	Single: 2274600-R	Single: 2274300-R
RAID Levels	Hardware RAID 0, 1, 1E, 5, 6, 10, 50, 60					Hardware RAID 0, 1, 1E, 5, 6, 10, 50, 60		
Bus Interface	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3
Processor	Microsemi 12 Gbps RoC	Microsemi 12 Gbps RoC	Microsemi 12 Gbps RoC	Microsemi 12 Gbps RoC	Microsemi 12 Gbps RoC	Microsemi 12 Gbps RoC	Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC
Hybrid RAID	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10
Form Factor	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile
Dimensions	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)
Ports	16 Internal	8 Internal 8 External	16 Internal	8 Internal 8 External	8 Internal	4 Internal	16 Internal	8 Internal
Maximum Scalability	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*
Connector	4 Internal SFF-8643	2 Internal SFF-8643/ 2 External SFF-8644	4 Internal SFF-8643	2 Internal SFF-8643/ 2 External SFF-8644	2 Internal SFF-8643	1 Internal SFF-8643	4 Internal SFF-8643	2 Internal SFF-8643
Cache	1024MB	1024MB	1024MB	1024MB	1024MB	1024MB	1024MB	1024MB
SSD Cache	maxCache 3.0	maxCache 3.0	—	—	—	—	maxCache 3.0	maxCache 3.0
Cache Protection	Flash backup (embedded) AFM-700 (included)	AFM-700 (included)	Flash backup embedded (similar to AFM-700)	AFM-700 (optional)	AFM-700 (optional)	AFM-700 (optional)	AFM-700 (included)	AFM-700 (included)

* 238 SSD/HDDs maximum. Remaining capacity is reserved for expanders and enclosure management.

Adaptec RAID 78165	Adaptec RAID 71685	Adaptec RAID 72405	Adaptec RAID 71605	Adaptec RAID 7805	Adaptec RAID 71605E
Single: 2280900-R	Single: 2274700-R	Single: 2274900-R	Single: 2274400-R	Kit: 2274200-R Single: 2274100-R	Single: 2274500-R



Hardware RAID 0, 1, 1E, 5, 6, 10, 50, 60					Hardware RAID 0, 1, 1E, 10
8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3	8-Lane PCIe Gen3
Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC	Microsemi 6 Gbps RoC
Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10	Hybrid RAID 1, 10
MD2-Low Profile	Half Length-Full Height	Half Length-Full Height	MD2-Low Profile	MD2-Low Profile	MD2-Low Profile
2.535"H x 6.6"L (64mm x 167mm)	4.198"H x 6.6"L (107mm x 167mm)	4.198"H x 6.6"L (107mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)	2.535"H x 6.6"L (64mm x 167mm)
8 Internal 16 External	16 Internal 8 External	24 Internal	16 Internal	8 Internal	16 Internal
256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*	256 SAS/SATA devices*
2 Internal SFF-8643/ 4 External SFF-8644	4 Internal SFF-8643/ 2 External SFF-8644	6 Internal SFF-8643	4 Internal SFF-8643	2 Internal SFF-8643	4 Internal SFF-8643
1024MB	1024MB	1024MB	1024MB	1024MB	256MB
-	-	-	-	-	-
AFM-700 (optional)	AFM-700 (optional)	AFM-700 (optional)	AFM-700 (optional)	AFM-700 (optional)	-

Microsemi Adaptec SAS Expander Card

Adaptec 82885T
Single: 2283400-R



Ports:	28 Internal / 8 External
Connectors:	7 x SFF-8643, 2 x SFF-8644
Form Factor:	MD2 - Low Profile
Dimensions:	2.535"H x 6.6"L (64mm x 167mm)
PCIe Slot Power:	Through PCIe x4 interface
Auxiliary Power Connector:	Yes

EXPANDER



Cables

		12 Gbps Internal		6 Gbps Internal			
		SFF-8643	SFF-8087	SFF-8482	SATA	SATA right angle	
Connector to End Device							
Connector to Adapter							
INTERNAL	Supported Products	SFF-8643 right angle	ACK-I-rA-HDmSAS-HDmSAS	ACK-I-rA-HDmSAS-mSAS	ACK-I-rA-HDmSAS-4SAS-SB	ACK-I-rA-HDmSAS-4SATA-SB	ACK-I-rA-HDmSAS-4rASATA-SB
			Part # 1 meter: 2282800-R Part # .5 meter: 2282500-R	Part # .8 meter: 2280200-R Part # .5 meter: 2281300-R	Part # .8 meter: 2279600-R	Part # .8 meter: 2280000-R	Part # .8 meter: 2279900-R
		SFF-8643	ACK-I-HDmSAS-HDmSAS	ACK-I-HDmSAS-mSAS	ACK-I-HDmSAS-4SAS-SB	ACK-I-HDmSAS-4SATA-SB	
			Part # 1 meter: 2282100-R Part # .5 meter: 2282200-R	Part # 1 meter: 2279700-R Part # .5 meter: 2281200-R	Part # .8 meter: 2280100-R	Part # .8 meter: 2279800-R	

		12 Gbps External	6 Gbps External
Connector to End Device		SFF-8644 External 	SFF-8088 External
Connector to Adapter			
EXTERNAL	Supported Products	ACK-E-HDmSAS-HDmSAS	ACK-E-HDmSAS-mSAS
		Part # 2 meters: 2282600-R	Part # 2 meters: 2280300-R

CABLES


Make the Right Connection with Microsemi Adaptec 12 Gbps and 6 Gbps SAS HD Cables

Microsemi Adaptec 12 Gbps (Series 8, HBA 1000) and 6 Gbps (Series 7) RAID adapters and HBAs are configured with mini-SAS HD connectors to allow for maximum performance and connectivity in a MD2-Low Profile form factor.

Pick the right cable for your internal or external storage solution.

Need more info?
Visit: www.microsemi.com





Customers, resellers and system integrators worldwide benefit from our superior reputation for technology innovation, reliability, local service and support. Contact us to learn more about our storage solutions.



Microsemi Corporate Headquarters

One Enterprise, Aliso Viejo, CA 92656 USA

Within the USA: +1 (949) 380-6100

Sales: +1 (949) 380-6136

Fax: +1 (949) 215-4996

Email: sales.support@microsemi.com

www.microsemi.com

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

MSCC HBA MPG-003-16

Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 4,800 employees globally. Learn more at www.microsemi.com

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.