

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

7-Port USB Charging Station with Quick Charge 3.0, USB-C Port, Device Storage, 5V 4A (60W) USB Charge Output

MODEL NUMBER: U280-007-CQC-ST











Charges and organizes up to 7 electronic devices at the same time. Storage compartment neatly organizes your excess cabling to reduce clutter when charging, and stores it out of the way when not in use. Recommended for quick-charging and storing tablets, smartphones and other mobile devices.

Description

Whether you're at home or in the office, Tripp Lite's U280-007-CQC-ST 7-Port USB Charging Station provides enough ports and power to keep your devices at 100% capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to seven tablets, smartphones and other devices at the same time. The U280-007-CQC-ST doesn't require a computer, so you can take it anywhere AC power is available.

The U280-007-CQC-ST features five USB-A ports, each capable of delivering up to 5V, 2.4A, which is enough for charging even battery-intensive devices like the Apple® iPad®. A USB-C port provides up to 5V, 3A for more powerful devices. Plus, a Quick Charge 3.0 port is capable of rapid-charging compliant devices up to four times faster than normal USB charging.

In addition, this charging station doubles as a storage unit by providing space to neatly organize cabling while your devices charge. When not in use, cables can be stored in the compartment and kept out of the way. The included adjustable brackets accommodate the number and size of the devices being charged.

To charge your USB devices, simply connect the five-foot power cord's NEMA 1-15P plug to an AC power outlet, and connect your devices to the available USB ports. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. Also, each USB-A port complies with USB Battery Charging (BC) specification v1.2. The brackets and power supply store conveniently in the charging station when not in use.

Features

Charges Up to 7 Devices at the Same TimeRecommended for charging tablets, smartphones and other devices at home or workFunctions anywhere AC power is available—no computer required **Provides Plenty of Juice for Charging**Quick Charge 3.0 Class A 5/9/12V technologyQC 3.0-compliant devices charge up to 4x faster than conventional USB chargingDelivers up to 5V, 2.4A per USB-A port—enough for charging battery-intensive devices like the Apple iPadUSB-C port provides up to 5V, 3A of charging powerProtects against overheating, overcurrent and overchargingComplies with USB Battery Charging (BC) specification v1.2

Highlights

- 5 USB-A ports provide up to 5V, 2.4A of charging power and are USB Battery Charging (BC) specification v1.2 compliant
- USB-C port provides up to 5V, 3A of charging power
- Quick Charge 3.0 port charges up to 4x faster than normal charging
- 9 adjustable storage brackets for organizing devices
- Storage compartment neatly organizes your cabling

Package Includes

- U280-007-CQC-ST 7-Port USB Charging Station
- (9) Storage brackets
- External power supply (Input: 100–240V, 50/60 Hz, 1.5A;

Output: 15V, 4A)

- C7 to NEMA 1-15P power cord, 5 ft.
- Quick Start Guide



Efficiently Stores Your Cables / Devices Too9 adjustable brackets provide space to neatly organize devices as they chargeConvenient storage compartment lets you neatly organize your cabling while your devices chargeWhen not in use, cables can be stored in the compartment and kept out of the way Easy to UseExternal dual-voltage power supply with C8 power inlet and detachable C7 to 1-15P 5 ft. cordNo computer required

Specifications

| OVERVIEW | | |
|---|--|--|
| UPC Code | 037332199577 | |
| Product Type | Charging Station | |
| Charging Form Factor | Charging Hub | |
| AC Adapter | Input: 100-240V, 50/60Hz, 1.5A; Output: 15V, 4A | |
| Device Compatibility | Phone; Tablet; Amazon Kindle | |
| Over Current Protection | Yes | |
| Technology | USB | |
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC; 230V AC | |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 | |
| Input Frequency | 50/60Hz | |
| Input Plug Type | NEMA 1-15P (NON-POLARIZED) | |
| Input Current | 1.5A | |
| External Power Supply Plug(s) | NEMA 1-15P North America | |
| OUTPUT | | |
| Output Capacity | 15V 4A | |
| Overload Protection | Yes | |
| BATTERY | | |
| Battery Charging (5V/1.5A Port) | Yes | |
| POWER | | |
| External Power Supply Input Specs (V / Hz / A) | 100-240V, 50/60Hz, 1.5A | |
| External Power Supply Output Specs (V / A) | 15V / 4A | |
| External Power Supply Cord Length (ft.) | 3 | |
| External Power Supply Cord Length (m.) | 1 | |



| External Power Supply DC Barrel Connector Specs | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve | |
|--|---|--|
| External Power Supply Certifications | CCC; FCC; GS; PSE; RoHS; TUV; UL; cUL | |
| USB Power Delivery (PD) Charging Support | Yes | |
| USB Power Delivery (PD) Charging Specification | 2.0 | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| LED Indicators | Blue (Power) | |
| CHARGING | | |
| Charging Ports / Amps | (5) 2.4A; (1) 3A; (1) 3A / 2A / 1.5A | |
| Number of Charging Ports | 7 | |
| Overcharge Protection | Yes | |
| Total Charging Amps | 9.1A | |
| Charging Method | USB | |
| Total Charging Watts | 60 | |
| Charging Ports Detail | USB-A: 5V/2.4AUSB-A QC: 3.6V~6.5V/3A, 6.5V~9V/2A, 9V~12V/1.5AUSB-C: 5V/3A | |
| Charging Port Type | (6) USB A (FEMALE); USB C (FEMALE) | |
| Charging Method Detail | Quick Charge 3.0; 5V - 1.5A (7W) | |
| PHYSICAL | | |
| Color | Black | |
| Material of Construction | Polycarbonate | |
| Shipping Dimensions (hwd / cm) | 7.11 x 16.00 x 25.91 | |
| Shipping Dimensions (hwd / in.) | 2.80 x 6.30 x 10.20 | |
| Shipping Weight (kg) | 0.91 | |
| Shipping Weight (lbs.) | 2.00 | |
| Unit Dimensions (hwd / cm) | 2.2 x 16.8 x 12.4 | |
| Unit Dimensions (hwd / in.) | 0.79 x 6.6 x 4.9 | |
| Unit Packaging Type | Box | |
| Unit Weight (kg) | 0.64 | |
| Unit Weight (Ibs.) | 1.4 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 41 to 95 F (5 to 35 C) | |
| Storage Temperature Range | -4 to 122 F (-20 to 50 C) | |
| | ·] | |



| Deletion Hereitite | | |
|--|-------------------------------|--|
| Relative Humidity | 20% to 80% RH, Non-Condensing | |
| Power Consumption (Watts) | 15.6 | |
| CONNECTIONS | | |
| CONNECTIONS | | |
| Ports | 7 | |
| Side A - Connector 1 | NEMA 1-15P (NON-POLARIZED) | |
| Side B - Connector 1 | (6) USB A (FEMALE) | |
| Side B - Connector 2 | USB C (FEMALE) | |
| FEATURES & SPECIFICATIONS | | |
| Quick Charge Compliant | 3.0 | |
| SPECIAL FEATURES | | |
| Overcurrent Protection | Yes | |
| Overvoltage Protection | Yes | |
| GaN Technology | No | |
| STANDARDS & COMPLIANCE | | |
| Certifications | FCC, REACH, RoHS | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | 2-year limited warranty | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies