

Single Bay Hard Drive Eraser, Standalone HDD/SSD Sanitizer, 4Kn, USB 3.0 to SATA III (6 Gbps), 9 Erase Modes, LCD Display, Secure Erase Hard Disk Sanitizer Dock, DB-9 Printer Port, TAA Compliant

Product ID: SDOCK1EU3P2



This hard drive eraser lets you wipe a SATA solid-state drive (SSD) or hard drive (HDD) without connecting to a host computer. It's compatible with 2.5" and 3.5" drives and supports SATA I, II, and III, and large capacity drives, including 4Kn drives.

You can rest easy when using this eraser to retire, re-use or re-purpose a drive. No data will remain on the drive and nothing will be accessible with data recovery software.

The SSD and HDD eraser supports nine erase modes to support a variety of security requirements, including:

- Quick Erase
- Single and Multi-pass Overwrites
- Custom Erase
- Secure Erase
- Enhanced Secure Erase

This drive eraser ensures data is purged (a secure erase) which is required by government agencies and organizations who have strict guidelines on deleting data. Purging is a very secure method of erasing data from your storage device which complies with the NIST 800-88 Rev. 1 media sanitation standard established by the National Institute of Standards and Technology

The hard drive eraser can connect to an RS232 serial printer to print a record of the erase procedure. The receipt shows the time and date of the erasure, and the erase mode used.

The LCD also lets you monitor erase performance and completion.



The eraser can be used as a SATA dock when connected to a USB 3.0 computer. It supports data transfer speeds of up to 5Gbps.

When used as a dock you can:

- · Back up a drive
- Test a drive
- Transfer data to a drive

SDOCK1EU3P2 is TAA compliant and backed by a StarTech.com 2-year warranty with free lifetime technical support.

Certifications, Reports and Compatibility















Applications

- IT technicians and business professionals who need to quickly and securely erase SSDs or HDDs
- System administrators, IT professionals and business administrators who need quick access to drives
- IT technicians who regularly test or benchmark different drives and need to swap between them

Features

- STANDALONE 4KN HARD DRIVE ERASER: This single-bay hard disk wiper / sanitizer features 4Kn sector drive compatibility, it works as a USB to SATA adapter, and it is capable of standalone harddrive erasing
- DRIVE COMPATIBILITY: Works with 2.5/3.5" HDD/SSD SATA drives of any capacity or file format; 4Kn Compatible; OS Independent; SATA III (6 Gbps); Compatible Drive Adapters: mSATA (SAT32MSAT257), SATA M.2 (SAT32M225) adapters sold separately
- ERASE MODES: 9 erase modes including Quick Erase, Single/3/7 Pass Overwrite, Custom Erase, Secure & Enhanced Secure Erase (meets NIST SP 800-88 Rev 1 clear/purge); DB-9 (RS232) Printer Port; USB 3.2 Gen 1 (5 Gbps); Toolless Design; TAA Compliant
- LCD MENU DISPLAY: Digital LCD Display with push button navigation for easy configuration and drive setup; Muti-function LEDs; Upgradeable firmware for future standards; Hardware includes 3ft (0.9m) USB 3.2 (5 Gbps) Type-A cable and Universal Power Adapter



• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this standalone hard drive eraser is backed for 2 years, including free lifetime 24/5 multilingual technical assistance

Hardware

Warranty 2 Years

Interface USB 3.2 Gen 1 (5Gbps)

Bus Type USB 3.2 Gen 1 (5Gbps)

Number of Drives 1

Drive Size 2.5in & 3.5in

Compatible Drive Types SATA

Drive Installation Removable

Chipset ID Xilinx - Spartan-6

Performance

Maximum Data Transfer

Rate

3Gbps

Type and Rate USB 3.0 - 5 Gbit/s

4Kn Support Yes

S.M.A.R.T. Support Yes

Type and Rate SATA III (6 Gbps)

Port Multiplier No

Max Drive Capacity Currently tested with up to 10TB 7200 RPM

Hot Swap Capability Yes

MTBF 8640 Hours

Connector(s)

Drive Connectors 2 - SATA Data & Power Combo (7+15 pin)

Host Connectors 1 - USB 3.2 Type-B (9 pin, Gen 1, 5Gbps)

Other Interface(s) 1 - DB 9-pin Serial

Software



	OS Compatibility	OS independent; No software or drivers required
Special Notes / Requirements		
·	Note	Receipt printing through the RS232 serial port requires a printer which supports the ESC/P printer control language.
Indicators	LED Indicators	1. 3 Line I CD display on top
	LED Indicators	1 - 2-Line LCD display on top
		1 - Power LED
		1 - Activity LED
		1 - HPA/DCO Detect LED
Power		
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	1.4 A
	Output Voltage	12V DC
	Output Current	5 A
	Center Tip Polarity	Positive
	Plug Type	M
	Power Consumption (In Watts)	60
Environmental		
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-10C to 65C (14F to 149F)
	Humidity	10% ~ 90% RH
Physical Characteristics		
	Color	Black
	Material	Steel
	Product Length	5.5 in [14 cm]



	Product Width	4.8 in [12.3 cm]
	Product Height	2.8 in [7 cm]
	Weight of Product	23.2 oz [656 g]
Packaging Information		
	Package Quantity	1
	Package Length	14.6 in [37.2 cm]
	Package Width	7.2 in [18.3 cm]
	Package Height	3.5 in [90 mm]
	Shipping (Package) Weight	4.5 lb [2.1 kg]
What's in the Box		
	Included in Package	1 - drive eraser and dock
		1 - USB 3.0 cable
		1 - universal power adapter (NA/JP, UK, EU, ANZ)
		1 - quick-start guide

^{*}Product appearance and specifications are subject to change without notice.