

ViewSonic® LED DISPLAY **XG240R**

Key Features

ELITE RGB BACKLIGHT | Tournament-Ready | ELITE GAME MODES | KEEPING IT TOGETHER | See clearly in dark areas



Product Description

The XG240R is the revamped successor to the ViewSonic XG2402 gaming monitor, integrating RGB accent lighting, and all the performance essentials needed for gamers to play competitively. A 144Hz refresh rate, 1ms response, and fully customisable settings provide all the essential performance specs and features necessary for the modern day competitive gaming environment. The XG240R is also the only 24" gaming monitor equipped with ELITE RGB, a unique RGB accent design on the back of the monitor, which can be controlled by other peripheral brands' software. This customised lighting setup will enhance your immersive play and sync up with your other peripherals.

Visit Us  www.viewsonic.com

LCD PANEL

Monitor Size:	24"W
Panel Technology:	TN TFT LCD
Resolution:	Full HD 1920 x 1080
Display Area:	531.4 mm (H) x 0.277 mm (V)
Aspect Ratio:	16:9
Brightness:	350 cd/m2
Contrast Ratio:	1000:1 (typ)
Dynamic Contrast Ratio:	120M:1
Viewing Angles:	170 degree / 160 degree (Typ)
Refresh Rate:	144Hz
Response Time:	GTG : 1ms
Backlight:	1 LED light bar
Backlight Life:	30000 Hrs (Min)
Colours:	16.7M colors (RGB 8-bit)
Pixel Size:	0.277 mm (H) x 0.277 mm (V)

INPUT SIGNAL

Frequency:	Fh = 15 ~ 160 KHz; Fv = 24 ~ 144 Hz
Sync:	TMDS,PCI-E

COMPATIBILITY

PC:	Windows 10 certified
Mac®:	Mac OS Tested

CONNECTOR

Input:	HDMI 1.4 x 2 DisplayPort 1.2 x 1
Output:	Earphone Out x 1 (3.5mm plug)

AUDIO

Speaker:	2W x 2
----------	--------

USB

Upstream:	USB 3.0 Type B x 1
Downstream:	USB 3.0 Type A x 2

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	45W (Typ) 50W (Max)
Optimize:	36W
Conserve:	31W

MODEL COLOUR

Black

ERGONOMICS

Tilt:	-5 ~ 20
Swivel:	-45 ~ 45
Pivot:	0 ~ 90
Height Adjustment:	120

WALL MOUNT

VESA®:	100 x 100mm
--------	-------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	566 mm (W) x 433.9~530.18 mm (H) x 239 mm (D)
Physical without stand (mm):	566 mm (W) x 341 mm (H) x 60 mm (D)
Packaging (mm):	640 mm (W) x 396 mm (H) x 207 mm (D)

WEIGHT

Net with stand:	6.7 Kg
Net without stand:	3.4 Kg
Gross:	8.5 Kg

REGULATIONS

cTUVus, FCC-B, ICES003, Energy Star, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, KC, e-Standby

WARRANTY

*Warranty offered may differ from market to market

PACKAGE CONTENTS

LCD Display
Power Cable (1.5m)
DisplayPort Cable (1.8m)
USB3.0 Cable (1.5m)
Quick Start Guide