

RackStation

RS820+

RS820RP+



High Performance 1U Rackmount NAS for Effective Data Storage and Management

Synology RackStation RS820+/RS820RP+ is an ideal network-attached storage solution for centralizing data management. Powered by a 4-core processor, RS820+/RS820RP+ provides both high performance and scalable storage, ideal for file sharing across different platforms and data backup. Synology RS820+/RS820RP+ is backed by Synology's 3-year limited warranty¹.

Highlights

- 4-core, 2.1 GHz CPU with AES-NI support. 2 GB DDR4 memory expandable up to 18 GB
- Outstanding 10GbE sequential performance at over 1,621 MB/s reading and 599 MB/s writing²
- Scale up to 8 drives with Synology Expansion Unit RX418³
- One PCIe 3.0 slot for an optional 10GbE add-in network interface card, or an M2D18 M.2 SSD adapter card⁴
- Advanced Btrfs file system offering 65,000 system-wide snapshots and 1,024 snapshots per shared folder
- Synology High Availability (SHA) providing continuous services with seamless transitioning between clustered servers

High Performance Storage with Scalability

Synology RS820+/RS820RP+ is a 1U rackmount 4-bay network-attached storage solution designed for businesses requiring an effective and centralized data management. It is equipped with a **4-core** processor and **2 GB** DDR4 memory, expandable up to **18 GB**. The **PCIe 3.0 slot** supports an **optional 10GbE** add-in network interface card, or an **M2D18 M.2 SSD adapter card**⁴, where the M.2 NVMe/SATA SSD cache can be used to boost system random IOPS.

With Link Aggregation enabled in a 10GbE environment, RS820+/RS820RP+ delivers high sequential throughput at over **1,621 MB/s reading** and **599 MB/s writing**². Storage capacity of RS820+/RS820RP+ can be further expanded with one **optional Synology Expansion Unit RX418**³, providing a raw capacity of up to **128 TB** with 8 drives in total.



Synology Active Backup Suite

Integrated, modern, and license-free backup together with an instant recovery solution for business workloads in physical, virtual, and cloud environments.

Ultimate Backup Solution

RS820+/RS820RP+ integrates various backup applications to safeguard your important data on any devices with an intuitive user interface and durable storage technologies.

- Workstation/Server/Virtual Machine/SaaS backup: **Active Backup for Business** centralizes backup tasks for virtual machines, Windows PC, servers, and rsync/SMB file servers and offers various recovery options to ensure lowest RTO. **Active Backup for Office 365/G Suite** is an on-premises backup solution for public clouds with a centralized dashboard, optimizing storage efficiency through the single instancing and block-level deduplication technology.
- NAS backup: **Hyper Backup** comprehensively backs up your data to a local shared folder, an external device, another Synology NAS, an rsync server, or Synology public cloud service, **Synology C2 Backup**⁵, to ensure data safety and availability can be achieved when a disaster happens
- Computer backup: **Synology Drive Client** backs up your Windows, Mac, and Linux desktop devices to safeguard important computer files. RS820+/RS820RP+ is also compatible with Time Machine, allowing you to effortlessly back up your Mac to Synology NAS.



Next-Generation File System

A modern file system designed to address obstacles often encountered in enterprise storage systems, safeguarding data integrity through metadata mirroring, self-healing and snapshot replication.

Btrfs: Next Generation Storage Efficiency

RS820+/RS820RP+ introduces **Btrfs file system**, bringing the most advanced storage technologies to meet the management needs of modern business:

- **Advanced snapshot technology** provides schedulable and near-instantaneous data protection of share folders and iSCSI LUNs.
- **File and folder level data restoration** brings great convenience and saves time for users who wish to restore only a specific file or folder.
- **Flexible Shared Folder and User Quota System** provide comprehensive quota control on all user accounts and shared folders.
- **File self-healing** allows Btrfs file system to auto-detect corrupted files with mirrored metadata, and to recover broken data using the supported RAID type of volumes, including RAID1, 5, 6, and 10.


Reliability, Availability, and Disaster Recovery

System reliability is critical for business everywhere. RS820+/RS820RP+ responds to these concerns with wide-ranging availability and redundancy features:


- **Synology High Availability** ensures seamless transitioning between clustered servers in unexpected disasters and ensures that your services remain online.
- **Snapshot Replication** provides schedulable, near-instantaneous data protection, ensuring that your business documents in shared folders, virtual machines in iSCSI LUNs, or dockerized application data remain safe and available in a disaster.
- **Redundant power supplies** (RS820RP+ only), **system fans** and **network ports** with failover support ensure continual service uptime.
- High reliability system design, including **fan-less CPU heat sink** and **passive cooling technology**, prevents single points of failure.
- Optional 5-year warranty¹ is available in select regions.

Hardware Overview


Front



Rear (RS820+)



Rear (RS820RP+)



1	Power button and indicator	2	Alert indicator	3	Drive status indicator	4	Beep off button
5	Status indicator	6	Drive tray	7	Console port	8	PCIe expansion slot
9	Power port	10	System fan	11	1GbE RJ-45 port	12	Reset button
13	USB 3.0 port	14	eSATA port				

Technical Specifications

Hardware

CPU	Intel Atom C3538 4-core 2.1GHz
Hardware encryption engine	Yes (AES-NI)
Memory	2 GB DDR4 Non-ECC onboard (expandable up to 18 GB) ⁶
Compatible drive type	4 x 3.5" or 2.5" SATA HDD/SSD (drives not included)
Hot swappable drive	Yes
External port	<ul style="list-style-type: none"> • 2 x USB 3.0 port • 1 x Expansion port
Size (HxWxD)	<ul style="list-style-type: none"> • RS820+: 44 x 430.5 x 457.6 mm / 44 x 480 x 492.6 mm (with server ears) • RS820RP+: 44 x 430.5 x 483.6 mm / 44 x 480 x 518.6 mm (with server ears)
Weight	<ul style="list-style-type: none"> • RS820+: 6.4 kg • RS820RP+: 7.96 kg
LAN	4 x Gigabit (RJ-45)
Wake on LAN/WAN	Yes
PCIe 3.0 slot	<ul style="list-style-type: none"> • 1 x 4-lane x8 slot • High-performance network interface card support • M.2 NVMe/SATA SSD adapter card support⁴
Scheduled power on/off	Yes
System fan	<ul style="list-style-type: none"> • RS820+: 3 (40 x 40 x 20 mm) • RS820RP+: 2 (40 x 40 x 20 mm)
AC input power voltage	100V to 240V AC
Power frequency	50/60Hz, single phase
Operating temperature	0°C to 35°C (32°F to 95°F)
Storage temperature	-20°C to 60°C (-5°F to 140°F)
Relative humidity	5% to 95% RH
Maximum operating altitude	5,000 m (16,400 ft)

General DSM specification

Networking protocol	SMB, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP)
File system	<ul style="list-style-type: none">Internal: Btrfs, ext4External: Btrfs, ext4, ext3, FAT, NTFS, HFS+, exFAT⁷
Supported RAID type	Synology Hybrid RAID (SHR), Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
Storage management	<ul style="list-style-type: none">Maximum single volume size: 108TBMaximum system snapshots: 65,536⁸Maximum internal volume: 256
SSD cache	<ul style="list-style-type: none">Read/write cache supportM.2 NVMe/SATA SSD support⁴
File sharing capability	<ul style="list-style-type: none">Maximum local user account: 2,048Maximum local group: 256Maximum shared folder: 512Maximum concurrent SMB/NFS/AFP/FTP connection: 500
Privilege	Windows Access Control List (ACL), application privilege
Directory service	Windows® AD integration: Domain users login via SMB/NFS/AFP/FTP/File Station, LDAP integration
Virtualization	VMware vSphere® 6.5, Microsoft Hyper-V®, Citrix®, OpenStack®
Security	Firewall, encryption shared folder, SMB encryption, FTP over SSL/TLS, SFTP, rsync over SSH, login auto block, Let's Encrypt support, HTTPS (customizable cipher suite)
Supported client	Windows 7 onwards, Mac OS X® 10.11 onwards
Supported browser	Chrome®, Firefox®, Edge®, Internet Explorer® 10 onwards, Safari® 10 onwards; Safari (iOS 10 onwards), Chrome (Android™ 6.0 onwards) on tablets
Interface language	English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, ไทย, 日本語, 한국어, 繁體中文, 简体中文

Packages and Applications

File Server & Synchronization

Synology Drive	Provide a universal portal to synchronize your files across various platforms, including Windows, macOS, Linux, Android and iOS. The built-in universal portal allows you to access data anytime and anywhere. <ul style="list-style-type: none">Maximum number of hosted files: 1,000,000Maximum number of concurrent connections for PC clients: 550
File Station	Virtual drive, remote folder, Windows ACL editor, compressing/extracting archived files, bandwidth control for specific users or groups, creating sharing links, transfer logs
FTP Server	Bandwidth control for TCP connections, custom FTP passive port range, anonymous FTP, FTP SSL/TLS and SFTP protocol, boot over the network with TFTP and PXE support, transfer logs
Presto File Server ⁹	High-speed data transfer over WAN with exclusive SITA technology between Synology NAS and desktop
Cloud Sync	One or two-way synchronization with public cloud storage providers including Alibaba Cloud OSS, Amazon Drive, Amazon S3-compatible storage, Backblaze B2, Baidu Cloud, Box, Dropbox, Google Cloud Storage, Google Drive, hubiC, MegaDisk, Microsoft OneDrive, OpenStack Swift-compatible storage, Tencent COS, WebDAV servers, Yandex Disk
Universal Search	Offer global search into applications and files

iSCSI Storage & Virtualization

iSCSI Manager	<ul style="list-style-type: none">Maximum iSCSI target: 128Maximum iSCSI LUN: 256iSCSI LUN clone/snapshot support
Virtual Machine Manager	Deploy and run various virtual machines on Synology NAS, including Windows, Linux, or Virtual DSM

Data Protection & Backup Solution

Hyper Backup	Support local backup, network backup, and backup data to public clouds
Backup tools	DSM configuration backup, macOS Time Machine support, Synology Drive Client desktop application Shared folder sync - maximum task number: 16
Snapshot Replication	<ul style="list-style-type: none">Maximum of shared folder snapshots: 1,024Maximum of Replication: 64
Synology High Availability	Reduce service downtime by setting up two identical NAS into one high-availability cluster
Active Backup for G Suite	Support G Suite My Drive and Team Drive backup and restoration

Active Backup for Office 365	Support Office 365 OneDrive for Business, mail, contacts, and calendar backup and restoration
Active Backup for Business	All-in-one backup solution designed for heterogeneous business IT environment, enabling IT admins to remotely manage and monitor protection over PC, servers and VM on one centralized console
Productivity & Collaboration	
Collaboration tools	Collaborate with instant message service Synology Chat, online editor Synology Office, and scheduling assistant Synology Calendar <ul style="list-style-type: none"> • Chat maximum user: 1,500 • Office maximum user: 1,800 • Calendar: support CalDAV and access via mobile devices
Note Station	Rich-text note organization and versioning, encryption, sharing, media embedding and attachments
Synology MailPlus Server	Secure, reliable, and private mail solution with high-availability, load balancing, security and filtering design (includes 5 free email account licenses; additional accounts require the purchasing of additional licenses)
Synology MailPlus	Intuitive webmail interface for Synology MailPlus Server, customizable mail labels, filters, and user interface
Multimedia	
Moments	Support smart AI album with facial and subject recognition, photo editing and sharing features, similar photo detection, auto-editing functions such as color correction and angle adjustments, and AI selection of the best photos. Mobile applications are available on iOS and Android devices.
Other packages	Video Station, Photo Station, Audio Station, iTunes® Server
Surveillance	
Surveillance Station	Maximum IP camera: 40 (total of 1,200 FPS at 720p, H.264) (including two free camera licenses; additional cameras require the purchasing of additional licenses)
All-in-One Server	
Synology Directory Server	Provide a flexible and cost-effective domain controller solution
Central Management System	Provide a single interface to manage and monitor multiple Synology NAS
VPN Server	Maximum connection: 30, supported VPN protocol: PPTP, OpenVPN™, L2TP/IPSec
Mail Server	Supported Mail Server Protocols: POP3, SMTP, IMAP, Support LDAP/AD account
Mail Station	Webmail interface for Mail Server to receive emails from multiple POP3 mailboxes, customizable SMTP server
Web Station	Virtual host (up to 30 websites), PHP/MariaDB®, third-party applications support
Other packages	DNS Server, RADIUS Server, Log Center
Others	
Storage Analyzer	Volume and quota usage, total size of files, volume usage and trends based on past usage, size of shared folders, large files, most recently modified files, least recently accessed files
Antivirus Essential	Full system scan, scheduled scan, white list customization, virus definition auto update
Other packages	Additional 3rd-party packages available on Package Center

Environment and Packaging

Environment safety	RoHS compliant
Package content	<ul style="list-style-type: none"> • RS820+/RS820RP+ main unit x 1 • Quick Installation Guide x 1 • Accessory pack x 1 • AC power cord x 1 (RS820+) / 2 (RS820RP+)
Optional accessories	<ul style="list-style-type: none"> • 4 GB DDR4-2666 SO-DIMM (D4NESO-2666-4G) • 16 GB DDR4-2666 SO-DIMM (D4ECSO-2666-16G) • Synology E10G17-F2/E10G18-T1/E10G18-T2 10Gbps Ethernet adapters • Synology M2D18 M.2 SSD adapter card • Synology Expansion Unit RX418 • Synology Rail Kit RKM114-Rail Kit Mounted / RKS1317-Rail Kit Sliding • VisualStation VS360HD, VS960HD • Surveillance Device License Pack • MailPlus License Pack • Virtual DSM License Pack
Warranty	3 years ¹

*Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

1. 5-year warranty is available as an optional bundle with EW202, a 2-year Extended Warranty service add-on. Visit https://www.synology.com/en-global/products/Extended_Warranty for more information on availability. The warranty period starts from the purchase date as stated on your purchase receipt. Visit <https://www.synology.com/company/legal/warranty> for more information.
2. Performance figures may vary depending on environment, usage, and configuration.
3. RS820+/RS820RP+ supports one Synology Expansion Unit RX418, sold separately.
4. RS820+/RS820RP+ supports M.2 NVMe/SATA SSD cache creation when using with Synology M2D18, sold separately.
5. Synology C2 Backup is purchased separately when you select Synology C2 cloud backup as your destination in Hyper Backup. Synology C2 Backup provides one-time 30-day free-trial for each Synology Account.
6. RS820+/RS820RP+ comes with 2 GB DDR4 Non-ECC onboard and can support up to 18 GB by adding one optional 16 GB SO-DIMM.
7. exFAT Access is purchased separately in Package Center.
8. System snapshot includes snapshots taken by iSCSI Manager, Snapshot Replication, and Virtual Machine Manager. Availability of these packages varies by model.
9. Presto File Server License is purchased separately in Package Center.

SYNOLOGY INC.

Synology creates network-attached storage, IP surveillance solutions, and network equipment that transform the way users manage data, conduct surveillance, and manage networks in the cloud era. By taking full advantage of the latest technologies, Synology aims to help users centralize data storage and backup, share files on-the-go, implement professional surveillance solutions, and manage networks in reliable and affordable ways. Synology is committed to delivering products with forward-thinking features and the best in class customer services.

Copyright © 2019, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice.

RS820+/RS820RP+-2019-ENU-REV003

Headquarters

Synology Inc. 9F., No.1, Yuandong Rd., Banqiao Dist., New Taipei City 220, Taiwan Tel: +886 2 2955 1814 Fax: +886 2 2955 1884

China

Synology Shanghai
200070, Room 201, No. 511 Tianmu W.
Rd., Jingan Dist. Shanghai, China

France

Synology France SARL
102 Terrasse Boieldieu (TOUR W)
92800 Puteaux, France
Tel: +33 147 176288

North & South America

Synology America Corp.
3535 Factoria Blvd SE #200 Bellevue,
WA98006, USA
Tel: +1 425 818 1587

United Kingdom

Synology UK Ltd.
Unit 5 Danbury Court, Linford Wood,
Milton Keynes, MK14 6PL, United Kingdom

Germany

Synology GmbH
Grafenberger Allee 295
40237 Düsseldorf, Deutschland
Tel: +49 211 9666 9666

Japan

Synology Japan Co., Ltd
4F, 3-1-2, Higashikanda, Chiyoda-ku,
Tokyo, 101-0031, Japan