

**BOSCH**

Invented for life



# FLEXIDOME MULTI 7000i

## A MULTI-DIRECTIONAL OVERVIEW OFFERING HIGHLY DETAILED INSIGHTS

### Built-in Artificial Intelligence

With Intelligent Video Analytics and Camera Trainer



Perimeter protection



Video analytics extremely resistant against shaking



Camera Trainer functionality



Alerts when needed



Quickly retrieve correct data

### Applications



Retail stores



Intersection



Rail stations

### Installation made simple



Project Assistant



Remote Portal



Compatible with modular accessories



Wireless Wi-Fi dongle connection via USB (Available mid 2021)



4 cameras, 1 cable



1 IP address

• Ease of installation • Data security

The new FLEXIDOME multi 7000i and FLEXIDOME multi 7000i IR\* are intelligent multi-directional cameras that combine four independent camera sensors, 3.3-7.7mm AVF lenses with a total resolution of 12 to 20 MP. They provide the ideal solution for wide area coverage like traffic intersections and building corners, where detailed insights of a scene are a must. What's more? The solution is highly

flexible and convenient: although the solution houses four independent camera sensors, it requires only a single network connection, a single IP address and a single Video Management System license.\*\* Each imager capitalizes on the Bosch IVA and Camera Trainer technologies utilizing the built-in Artificial Intelligence, taking data usage to a whole new level.

\*IR model available July 2021. \*\*Depends on VMS partner.

# FLEXIDOME multi 7000i











FLEXIDOME multi 7000i  
12 MP | 20 MP



July

FLEXIDOME multi 7000i IR  
12 MP | 20 MP

## Specifications

| FLEXIDOME multi 7000i | <br>4 x 3MP | <br>4 x 5MP | <br>AVF | <br>120dB | <br>30 | <br>IR | <br>MIC | <br>-58°F to +131°F<br>-50°C to +55°C |
|-----------------------|--|--|--|--|---|---|--|--|
| NDM-7702-A            | ●  |  | ●  | ●  | 30  |   | ●  | -58°F to +131°F<br>-50°C to +55°C  |
| NDM-7703-A            |  | ●  | ●  | ●  | 30  |   | ●  | -58°F to +131°F<br>-50°C to +55°C  |
| NDM-7702-AL           | ●  |  | ●  | ●  | 30  | ●   | ●  | -58°F to +131°F<br>-50°C to +55°C  |
| NDM-7703-AL           |  | ●  | ●  | ●  | 30  | ●   | ●  | -58°F to +131°F<br>-50°C to +55°C  |

## Product Details

| Bosch #     | Description   |
|-------------|---|
| NDM-7702-A  | Multi-imager fixed dome 12MP 4x 3MP, 30FPS, 3.7-7.7mm AVF lens, IP66, IK10, Integrated MIC, IVA, Camera Trainer                             |
| NDM-7703-A  | Multi-imager fixed dome 20MP 4x 5MP, 30FPS, 3.7-7.7mm AVF lens, IP66, IK10, Integrated MIC, IVA, Camera Trainer                             |
| NDM-7702-AL | Multi-imager fixed dome 12MP 4x 3MP, 30FPS, 3.7-7.7mm AVF lens, IP66, IK10, Integrated MIC, IVA, Camera Trainer, integrated IR up to 98 ft. |
| NDM-7703-AL | Multi-imager fixed dome 20MP 4x 5MP, 30FPS, 3.7-7.7mm AVF lens, IP66, IK10, Integrated MIC, IVA, Camera Trainer, integrated IR up to 98 ft. |