







SPECIFICATIONS

| Panel Size | 27" |
|--|--|
| Active Display Area (mm) | 597.888(H) x 336.312(V) |
| Curvature | Flat |
| Panel Type | Rapid IPS |
| Panel Resolution | 1920 x 1080 (FHD) |
| Pixel Pitch (H x V) | 0.3114 (H) x 0.3114 (V) |
| Aspect Ratio | 16:9 |
| Brightness (nits) | SDR: 300 cd/m2 |
| Contrast Ratio | 1000:1 |
| DCR | 100000000:1 |
| Signal Frequency | 30~230 KHz(H) / 48~200 Hz(V) |
| ACTIVATED RANGE | 48~200Hz |
| Refresh Rate | 200Hz |
| Response time | 0.5ms (GtG, Min) |
| DYNAMIC REFRESH RATE TECHNOLOGY | AMD FreeSync™ Premium |
| HDR Support | HDR Ready |
| Video ports | 1x HDMI™ 2.0b (FHD@200Hz) 1x DisplayPort 1.2a (HBR2) |
| USB ports | N/A |
| h | |
| Audio ports | 1x Headphone-out |
| <u>-</u> | 1x Headphone-out 178° (H) / 178° (V) |
| Audio ports | |
| Audio ports Viewing Angle | 178° (H) / 178° (V) |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI TM CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type Power Input | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board 100~240V, 50/60Hz |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type Power Input Adjustment (Tilt) | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board 100~240V, 50/60Hz -5°~20° |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type Power Input Adjustment (Tilt) Adjustment (Swivel) | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board 100~240V, 50/60Hz -5°~20° N/A |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type Power Input Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board 100~240V, 50/60Hz -5°~20° N/A N/A |
| Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Console Mode Power Type Power Input Adjustment (Tilt) Adjustment (Swivel) Adjustment (Height) | 178° (H) / 178° (V) 90% / 91% / 115% (CIE1976 Standard) Anti-glare 1.07B, 10 bits (8 bits + FRC) N/A Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported Internal Power Board 100~240V, 50/60Hz -5°~20° N/A N/A N/A |

FEATURES



Rapid IPS

Make sure the intensity and purity of colors when gaming.

200Hz High Refresh Rate



200Hz High Refresh Rate Experience smooth gaming with a blazing fast 200Hz refresh rate, that gives you the upperhand in fast moving games.



0.5ms (GtG, Min.) Response Time

Eliminate screen tearing and choppy frame rates with 0.5ms (GtG, Min.) Response Time.



DR Ready

Enhance eye-catching details through adjustments in contrast and shadows.



Console Mode

Optimized for seamless compatibility with gaming consoles like PS5 and Xbox Series X|S.



AI Vision

Smart black tuner to brighten your day by bringing out the fine details in dark areas.



MONITORS MAG 272F

| Dimension with Stand (W \times D \times H) | 612.6 x 249.8 x 440 mm (24.1 x 9.8 x 17.3 inch) |
|--|---|
| Dimension without Stand (W x D x H) | 612.6 x 54 x 364.8 mm (24.1 x 2.1 x 14.3 inch) |
| Weight (NW / GW) | 3.9 kg (8.5 lbs) / 6.2 kg (13.6 lbs) |
| Carton Dimension (W X D X H) | 668 x 131 x 446mm (26.2 x 5.1 x 17.5 inch) |
| Accessories | 1x HDMI™ Cable (2.0), 1x Power Cord (C13), 1x Power Adaptor, 1x Quick Guide |
| Note | HDMI™: 1920 x 1080 (Up to 200Hz) DisplayPort: 1920 x 1080 (Up to 200Hz) Support: HDMI™ CEC; Non Support: KVM, PIP/PBP |

CONNECTIONS



- 1. 5-way Joystick Navigator
- 2. AC-in
- 3. 2x HDMI™ 2.0b (FHD@200Hz)
- 4. Display Port 1.2a (HBR2)
- 5. Headphone out
- 6. Kensington Lock