# Product data sheet

Specifications

**Green Premium™**

## Rack PDU, Basic, 1U, 14.4kW, 208V, (6) C19

AP7516

## Overview

| | |
|---|---|
| Lead time | Usually in Stock |

## Main

| | |
|---|---|
| Color | Black |
| Product or Component Type | PDU |
| PDU Type | Basic |
| Cord length | 8 ft (2.4 m) |
| Provided Equipment | Installation guide<br>Rack Mounting brackets |

## Complementary

| | |
|---|---|
| Input Voltage | 208 V 3 phase |
| Height | 1.7 in (4.4 cm) |
| Width | 17.2 in (43.7 cm) |
| Output Voltage | 200 V<br>208 V |
| Depth | 10.0000000000 in (25.4 cm) |
| Net Weight | 17.59 lb(US) (7.98 kg) |
| mounting location | Front<br>Rear |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |
| Rack units | 1U |
| Mounting position | Horizontal |
| Line Rated Current | 40 A |
| Input current limits | 50 A |
| Load Capacity | 14400 VA |
| Input Frequency | 50/60 Hz |
| Number of input connectors | 1 CS8365 |
| Outlet type and quantity | 6 IEC 60320 C19 |

## Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Life Is On | Schneider Electric

| | |
|---|---|
| **Product Certifications** | cUL Listed<br>METI Denan<br>UL Listed |
| **Standards** | CSA C22.2 No. 60950-1-03<br>UL 60950-1 |
| **Ambient Air Temperature for Operation** | 23.0000000000…113.0000000000 °F (-5…45 °C) |
| **Relative Humidity** | 5…95 % |
| **Operating altitude** | 0...10000 ft |
| **Ambient Air Temperature for Storage** | -13.0000000000…149.0000000000 °F (-25…65 °C) |
| **Storage Relative Humidity** | 5…95 % |
| **Storage altitude** | 0…50000 ft (0.0000000000…15240.0000000000 m) |

# Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304232674 |
| **Country of origin** | IN |

# Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 9.5 in (24.1 cm) |
| **Package 1 Width** | 19.8 in (50.2 cm) |
| **Package 1 Length** | 22.008 in (55.9 cm) |
| **Package 1 Weight** | 22.3 lb(US) (10.1 kg) |

# Contractual warranty

| | |
|---|---|
| **Warranty** | 2 years repair or replace |

Life Is On | Schneider Electric

# Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Energy Efficient    Take-back    Transparency    RoHS/REACh

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Lead Free

## Certifications & Standards

**Reach Regulation**        REACh Declaration

**Eu Rohs Directive**        Compliant

EU RoHS Declaration

**Environmental Disclosure**        Product Environmental Profile

**Circularity Profile**        End of Life Information