



AV54LTW-28

Camera	Video Output Mode	AHD/CVI/TVI/CVBS 4 IN 1
	Image Sensor	1/2.9" CMOS Sensor
	Image Resolution	2MP 1080P/960H
	Effective Pixels	1920x1080
	TV System	PAL/NTSC
	Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
	S/N Ratio	≥50dB
	Scanning System	Progressive Scan
Lens	Focus Length	2.8mm
	Focus Control	Fixed
	Lens Type	Fixed
	Pixels	5M Pixels
Night Vision	Infrared LED	14μ x 12PCS
	Infrared Distance	66 Feet
	IR Status	Under 10 Lux by CDS
	IR Power On	CDS Auto Control
Camera Features	Day/Night	YES
	Multiple language OSD	YES
	White Balance	AUTO / MANUAL
	Gain Control	AUTO
	Noise Reduction	3DNR
	Picture Adjustment	YES
	WDR	YES
	OSD Support	YES
General	UTC	YES
	Housing	Metal, IP66
	IR Cut Filter	YES
	Operation Temperature	-10℃ ~ +50℃ RH95% Max
	Storage Temperature	-20℃ ~ +60℃ RH95% Max
	Power Source	DC12V±10%, 550mA
	Dimension	3.7 x 3.7 x 2.9 Inch
	Weight	0.9 LB




02.1

Install the metal plate to the wall or ceiling with screws.




02.2

Find three screws on the back of the camera, then insert them into the opening on the metal plate.



02.3

Twist the camera to lock it to the metal plate.




03.1

You have three options to record or view your video.


1. Connect the camera video out to your DVR video in.
2. Connect the camera video out to AVUE CCTV monitor

(for example: AVG22QHD-3D).

3. Connect the camera video to TV or other HDMI Monitor through the AVUE TVI/CVI/AHD to HDMI Converter (for example: TVH-L11).


**03.2**

The camera's default output is HD-TVI, if you do not see the video on your monitor, please use the DIP switch to change the signal that matches to your DVR.

**HD Mini Dome Camera**

User Manual

AV54LTW-28

**Features:**

2.8mm fixed lens mini dome camera uses advanced imaging technology with resolution as high as 1080P. If your DVR system is standard definition you can change the camera video out put to analog. (Please refer to step 03.2.) Employing latest digital signal processor, this dome camera also comes with a powerful OSD menu that features BLC, ATW, DNR, DWDR, Auto day/night, and more.

- 1/2.9" CMOS Sensor
- HD-TVI/AHD/CVI
- Supports CVBS (SD)
- 2MP 1080/960H
- 2.8 mm Fixed Lens
- Matrix IR
- Up to 66ft. IR Distance
- Digital Noise Reduction
- Digital Wide Dynamic Range
- Multiple language OSD (includes English, Spanish, French, Portuguese, Chinese, and Korean.)

Package includes:

Mini HD Dome Camera.....	1Pc
Camera Manual.....	1Pc
Drill Template.....	1Pc
Mounting Screws Kit.....	1Pc